

CLAIMS

- 10001957-130501
1. A pneumatic tire comprising  
a tread portion provided with at least one longitudinal groove extending in the tire circumferential direction and blocks adjacent to one side of said at least one longitudinal groove,  
each said block provided with a cut-slope on a corner between the top surface and a lateral face of the block, said lateral face facing the longitudinal groove,  
said cut-slope inclining towards the bottom of the longitudinal groove, and  
the axial width of the cut-slope gradually decreasing from a middle point of the cut-slope towards each side thereof in the circumferential direction.
  2. A pneumatic tire according to claim 1, wherein  
the maximum of the axial width at the middle point is in a range of from 20 to 40 % of a groove bottom width of the longitudinal groove at said bottom.  
in a tire meridian section, the cut-slope has an inclination angle of from 40 to 70 degrees with respect to the normal direction to the tread surface.
  3. A pneumatic tire according to claim 1, wherein  
the circumferential length of the cut-slope is in a range of from 50 to 80 % of the circumferential length of said corner of the block.
  4. A pneumatic tire according to claim 1, wherein  
said block provided with an axial groove extending from

said middle point and terminating in the block.

5. A pneumatic tire according to claim 1, wherein  
said at least one longitudinal groove is a  
circumferentially continuously extending substantially straight  
groove disposed on one side of the tire equator, and  
said blocks are disposed on the other side than the tire  
equator side of the longitudinal groove.

6. A pneumatic tire according to claim 5, wherein  
each said block is such that the circumferential length is  
greater than the axial width, and  
on the other side of the longitudinal groove, second  
blocks are disposed wherein each said second block is such that  
the axial width is greater than the circumferential length.